

ME132MA-4 7,5KW 400/690V B3

Three-phase asynchronous motor in aluminum

Motor type ME132MA-4 7,5KW 400/690V B3
Brand BUSCK
Item number 83041331

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	7,5	50	14,6	1450
690	7,5	50	8,4	1450
460	8,63	60	14,6	1740


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 49,4
Starting torque ratio 2,8
Pull out torque ratio 2,7
Starting current ratio 7,7

Note IE2 Färg svart

Efficiency class IE2
Efficiency, load 100% 88,81
Efficiency, load 75% 89,4
Efficiency, load 50% 88,5
Power fact, load 100% 0,84

Painting Standard
Color RAL 9005
Weight kg 53
Sound pressure Lp dB(A) 71
Bearing DE 6308-2Z/C3
Bearing NDE 6208-2Z/C3
Balance grade Normal
Inertia kgm² 0,03
Cable entries 2xM25



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no