


WE355L-4 315KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type WE355L-4 315KW 400/690V B3
 Brand BUSCK
 Item number 83043561

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	315	50	534,0	1490
690	315	50	307,1	1490
460	362,25	60	534,0	1788

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	95,7
Insulation class	F	Efficiency, load 75%	95,2
Cooling	IC411 (TEFC)	Efficiency, load 50%	94
Max. ambient temp.	40°C	Power fact, load 100%	0,89
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	1975
Torque, Nm	2019	Sound pressure Lp dB(A)	80
Starting torque ratio	2,1	Bearing DE	NU322
Pull out torque ratio	2,2	Bearing NDE	6322
Starting current ratio	6,9	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	9,1
		Cable entries	2xM63 + 1xM16
Note	Axel 100x210		



A	B	B1	C	H	D	E	F	G	DH	GA	AA	AB	AC	HA	HD	BB	LD	L
610	630	630	254	355	100	210	28	90	M24	106	116	726	698	52	997	750	288	1596