

ME132MA-6 4KW 400/690V B3

Three-phase asynchronous motor in aluminum

Motor type ME132MA-6 4KW 400/690V B3
Brand BUSCK
Item number 83061331

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	4	50	8,86	960
690	4	50	5,09	960
460	4,6	60	8,86	1152


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 39,8
Starting torque ratio 2,4
Pull out torque ratio 2,7
Starting current ratio 6,2

Note IE2 Färg svart

Efficiency class IE2
Efficiency, load 100% 84,9
Efficiency, load 75% 85,7
Efficiency, load 50% 84,6
Power fact, load 100% 0,77

Painting Standard
Color RAL 9005
Weight kg 50
Sound pressure Lp dB(A) 68
Bearing DE 6308-2Z/C3
Bearing NDE 6208-2Z/C3
Balance grade Normal
Inertia kgm² 0,0365
Cable entries 2xM25



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no