

WE315LB-4 200KW 230/400V B35


Three-phase asynchronous motor in cast iron

Motor type WE315LB-4 200KW 230/400V B35
 Brand BUSCK
 Item number 83A43184

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	200	50	626,1	1485
400	200	50	360,0	1485
460	230	60	360,0	1782

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	95,2
Insulation class	F	Power fact, load 100%	0,88
Cooling	IC411 (TEFC)	Painting	Standard
Max. ambient temp.	40°C	Color	RAL 9005
Min. ambient temp.	-20°C	Weight kg	1200
Max. temp. rise	80 K	Sound pressure Lp dB(A)	76
Max altitude, masl	1000	Bearing DE	NU319
		Bearing NDE	6319
Torque, Nm	1286	Balance grade	Normal
Starting torque ratio	2,1	Inertia kgm ²	4,856
Pull out torque ratio	2,2	Cable entries	2xM63, 1xM16
Starting current ratio	6,9		
Winding protection	Thermistors		

Note Shaft 90x170 mm
 IE2



A	B	B1	C	H	D	E	F	GA	DH	M	N	P	AB	AC	HA	HD	BB	LD	L
508	457	508	216	315	90	170	25		M20	600	550	660	628	680		680			1385