

WE280M-6 55KW 230/400V B35


Three-phase asynchronous motor in cast iron

Motor type WE280M-6 55KW 230/400V B35
 Brand BUSCK
 Item number 83A62814

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	55	50	171,2	985
400	55	50	98,4	985
460	63,25	60	98,4	1182

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	93,2
Insulation class	F	Power fact, load 100%	0,86
Cooling	IC411 (TEFC)	Painting	Standard
Max. ambient temp.	40°C	Color	RAL 9005
Min. ambient temp.	-20°C	Weight kg	545
Max. temp. rise	80 K	Sound pressure Lp dB(A)	66
Max altitude, masl	1000	Bearing DE	6317
		Bearing NDE	6314
Torque, Nm	533	Balance grade	Normal
Starting torque ratio	2,1	Inertia kgm ²	1,965
Pull out torque ratio	2,5	Cable entries	2xM63 + 1xM16
Starting current ratio	7		
Winding protection	Thermistors		

Note IE2



A	B	B1	C	H	D	E	F	GA	DH	M	N	P	AB	AC	HA	HD	BB	LD	L
457	419		190	280	75	140	20	79.5	M20	500	450	550	542	550	35	681	490	221	1020