

WE355L-8 200KW 230/400V B35


Three-phase asynchronous motor in cast iron

Motor type WE355L-8 200KW 230/400V B35
 Brand BUSCK
 Item number 83A83574

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	200	50	666,1	745
400	200	50	383,0	745
460	230	60	383,0	894

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	95
Insulation class	F	Power fact, load 100%	0,83
Cooling	IC411 (TEFC)	Painting	Standard
Max. ambient temp.	40°C	Color	RAL 9005
Min. ambient temp.	-20°C	Weight kg	2060
Max. temp. rise	80 K	Sound pressure Lp dB(A)	70
Max altitude, masl	1000	Bearing DE	NU322
Torque, Nm	2564	Bearing NDE	6322
Starting torque ratio	2	Balance grade	Normal
Pull out torque ratio	2	Inertia kgm ²	14,9
Starting current ratio	6,4	Cable entries	2xM63 + 1xM16

Note Axel 100x210



A	B	B1	C	H	D	E	F	GA	DH	M	N	P	AB	AC	HA	HD	BB	LD	L
610	630	630	254	355	100	210	28	106	M24	740	680	800	726	698	52	1000	750	288	1596