


SWE160MA-2 11KW 400/690V B35

Three-phase asynchronous motor in cast iron

Motor type SWE160MA-2 11KW 400/690V B35
Brand BUSCK
Item number 93021604w

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	11	50	19,3	2935
690	11	50	11,1	2935
460	12,65	60	19,3	3522

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	91,6
Insulation class	F	Efficiency, load 75%	91,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	90,5
Max. ambient temp.	40°C	Power fact, load 100%	0,90
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	113
Torque, Nm	35,8	Sound pressure Lp dB(A)	69
Starting torque ratio	2,7	Bearing DE	6209-2Z/C3
Pull out torque ratio	2,6	Bearing NDE	6209-2Z/C3
Starting current ratio	7,6	Balance grade	Normal
		Inertia kgm ²	0,0655
Note	IE3, Kopplingslåda med kabelanslutning Cable entry 40 + 1 x M16 2 x M32 + 1 x M16 (FL13)		



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no