

SWE250M-2 55KW 400/690V B5

Three-phase asynchronous motor in cast iron

Motor type SWE250M-2 55KW 400/690V B5
Brand BUSCK
Item number 93022502

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	55	50	91,8	2965
690	55	50	52,8	2965
460	63,25	60	91,8	3558

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	95
Insulation class	F	Efficiency, load 75%	95,2
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,2
Max. ambient temp.	40°C	Power fact, load 100%	0,91
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	391
Torque, Nm	177	Sound pressure Lp dB(A)	81
Starting torque ratio	2,1	Bearing DE	6313
Pull out torque ratio	2,4	Bearing NDE	6313
Starting current ratio	7,6	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,435
		Cable entries	2xM63 + 1xM16 (FL21)
Note	IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16 Färg svart		

