

T3CR250M-2 55KW 400/690V B5

Three-phase asynchronous motor in cast iron

Motor type T3CR250M-2 55KW 400/690V B5
Brand BUSCK
Item number 93022502T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	55	50	93,5	2960
690	55	50	53,8	2960
460	63,25	60	93,5	3552

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	94,3
Insulation class	F	Efficiency, load 75%	94,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	93,1
Max. ambient temp.	45°C	Power fact, load 100%	0,90
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	177,45	Weight kg	428
Starting torque ratio	2,5	Sound pressure Lp dB(A)	93
Pull up torque ratio	1,4	Bearing DE	6314 C3
Pull out torque ratio	2,6	Bearing NDE	6314 C3
Starting current ratio	10	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,44434
This motor has DNV type approval		Cable entries	2xM63, 1xM16

Note IE3

