

# T3A160M-4 11KW 400/690V B5


## Three-phase asynchronous motor in aluminum

Motor type T3A160M-4 11KW 400/690V B5  
 Brand BUSCK  
 Item number 93041602

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	11	50	20,9	1470
690	11	50	12,02	1470
460	12,65	60	20,9	1764

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	91,4
Insulation class	F	Efficiency, load 75%	91,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	89,8
Max. ambient temp.	40°C	Power fact, load 100%	0,83
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	89
Torque, Nm	71,46	Sound pressure Lp dB(A)	75
Starting torque ratio	2,6	Bearing DE	6309-2Z/C3
Pull up torque ratio	1,8	Bearing NDE	6209-2Z/C3
Pull out torque ratio	2,8	Balance grade	Normal
Starting current ratio	7,6	Inertia kgm <sup>2</sup>	0,1053728
Winding protection	Thermistors	Cable entries	2xM32, 1xM16

Note IE3 Färg svart



**BUSCK**  
[www.busck.eu](http://www.busck.eu)

Busck & Co AB  
 Gamla Riksvägen 14  
 428 32 Göteborg  
 Sweden  
 556027-1990  
[info@busck.se](mailto:info@busck.se)

Busck & Co ApS  
 Postboks 108  
 0900 København C  
 Denmark  
[info@busck.eu](mailto:info@busck.eu)

Busck AS  
 Skibåsen 35C  
 4636 Kristiansand  
 Norway  
[info@busck.no](mailto:info@busck.no)