

T3A160L-4 15KW 400/690V B35


Three-phase asynchronous motor in aluminum

Motor type T3A160L-4 15KW 400/690V B35
Brand BUSCK
Item number 93041614

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	15	50	27,7	1470
690	15	50	15,9	1470
460	17,25	60	27,7	1764

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	92,1
Insulation class	F	Efficiency, load 75%	92,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	91,3
Max. ambient temp.	45°C	Power fact, load 100%	0,85
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	110,5
Torque, Nm	97,45	Sound pressure Lp dB(A)	75
Starting torque ratio	3,0	Bearing DE	6309-2Z/C3
Pull up torque ratio	2	Bearing NDE	6209-2Z/C3
Pull out torque ratio	3	Balance grade	Normal
Starting current ratio	9,2	Inertia kgm ²	0,1370381
Winding protection	Thermistors	Cable entries	2xM32, 1xM16
This motor has DNV type approval			

Note IE3 Färg svart



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no