

T3CR180L-4 22KW 400/690V B35

Three-phase asynchronous motor in cast iron

Motor type T3CR180L-4 22KW 400/690V B35
 Brand BUSCK
 Item number 93041814T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	22	50	38,4	1460
690	22	50	22,1	1460
460	25,3	60	38,4	1752

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	93
Insulation class	F	Efficiency, load 75%	93,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	92,9
Max. ambient temp.	45°C	Power fact, load 100%	0,89
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	143,90	Weight kg	196
Starting torque ratio	2,5	Sound pressure Lp dB(A)	76
Pull up torque ratio	1,8	Bearing DE	6311 C3
Pull out torque ratio	3	Bearing NDE	6311 C3
Starting current ratio	10	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,19433
This motor has DNV type approval		Cable entries	2xM32, 1xM16

Note IE3

