

T3C355M-4 250KW 400/690V B35


Three-phase asynchronous motor in cast iron

Motor type T3C355M-4 250KW 400/690V B35
Brand BUSCK
Item number 93043554T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	250	50	422,0	1480
690	250	50	242,7	1480
460	287,5	60	422,0	1776

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	96
Insulation class	F	Efficiency, load 75%	96,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	95,4
Max. ambient temp.	40°C	Power fact, load 100%	0,89
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	1723
Torque, Nm	1613	Sound pressure Lp dB(A)	101
Starting torque ratio	2	Bearing DE	63322 C3
Pull up torque ratio	1,3	Bearing NDE	6322 C3
Pull out torque ratio	2,3	Balance grade	Normal
Starting current ratio	8	Inertia kgm ²	7,6382
Winding protection	Thermistors	Cable entries	2xM63, 1xM16
This motor has DNV type approval			

Note IE3



TYPE	D	E	F	G	DH	ED	L
355M/L-4/6/8P	Ø100	210	28-0,052	90	M24x50	160	1570

BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no