

SWE200LB-6 22KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type SWE200LB-6 22KW 400/690V B3
Brand BUSCK
Item number 93062011

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	22	50	42,3	985
690	22	50	24,3	985
460	25,3	60	42,3	1182

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	92,6
Insulation class	F	Efficiency, load 75%	92,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	91,2
Max. ambient temp.	40°C	Power fact, load 100%	0,81
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	240
Torque, Nm	213	Sound pressure Lp dB(A)	59
Starting torque ratio	2,2	Bearing DE	6312
Pull out torque ratio	2,2	Bearing NDE	6212
Starting current ratio	7,4	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,435
		Cable entries	2xM50 + 1xM16 (FL21)
Note	IE3, Kopplingslåda med FL21, 2x M50 + 1 x M16 Färg svart		

