

T3CR200LB-6 22KW 400/690V B35

Three-phase asynchronous motor in cast iron

Motor type T3CR200LB-6 22KW 400/690V B35
Brand BUSCK
Item number 93062014T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	22	50	42,5	970
690	22	50	24,5	970
460	25,3	60	42,5	1164

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	92,2
Insulation class	F	Efficiency, load 75%	93
Cooling	IC411 (TEFC)	Efficiency, load 50%	91,3
Max. ambient temp.	45°C	Power fact, load 100%	0,81
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	217	Weight kg	240
Starting torque ratio	2,5	Sound pressure Lp dB(A)	76
Pull up torque ratio	1,5	Bearing DE	6312 C3
Pull out torque ratio	2,8	Bearing NDE	6312 C3
Starting current ratio	10	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	0,44941
This motor has DNV type approval		Cable entries	2xM50, 1xM16

Note IE3

