

SWE250M-6 37KW 400/690V B5

Three-phase asynchronous motor in cast iron

Motor type SWE250M-6 37KW 400/690V B5
Brand BUSCK
Item number 93062502

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	37	50	67,3	985
690	37	50	38,7	985
460	42,55	60	67,3	1182

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	93,8
Insulation class	F	Efficiency, load 75%	93,9
Cooling	IC411 (TEFC)	Efficiency, load 50%	93
Max. ambient temp.	40°C	Power fact, load 100%	0,85
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	390
Torque, Nm	359	Sound pressure Lp dB(A)	59
Starting torque ratio	2,2	Bearing DE	6314
Pull out torque ratio	2,2	Bearing NDE	6313
Starting current ratio	7,2	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,113
		Cable entries	2xM63 + 1xM16 (FL21)

Note IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16
Färg svart

