

SWE280M-6 55KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type SWE280M-6 55KW 400/690V B3
Brand BUSCK
Item number 93062811

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	55	50	99,8	985
690	55	50	57,4	985
460	63,25	60	99,8	1182

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	94,7
Insulation class	F	Efficiency, load 75%	94,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	93
Max. ambient temp.	40°C	Power fact, load 100%	0,84
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	562
Torque, Nm	533	Sound pressure Lp dB(A)	60
Starting torque ratio	2,2	Bearing DE	6317
Pull out torque ratio	2,2	Bearing NDE	6314
Starting current ratio	6,8	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	1,988
		Cable entries	2xM63 + 1xM16 (FL21)

Note IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16
Färg svart

