

SWE315S-6 75KW 400/690V B5

Three-phase asynchronous motor in cast iron

Motor type SWE315S-6 75KW 400/690V B5
Brand BUSCK
Item number 93063152

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	75	50	134,0	985
690	75	50	77,1	985
460	86,25	60	134,0	1182

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	95,2
Insulation class	F	Efficiency, load 75%	95,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	94
Max. ambient temp.	40°C	Power fact, load 100%	0,85
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	905
Torque, Nm	727	Sound pressure Lp dB(A)	68
Starting torque ratio	2,3	Balance grade	Normal
Pull out torque ratio	2,3	Inertia kgm ²	3,864
Starting current ratio	7,1	Cable entries	2xM63 + 1xM16 (FL21)
Winding protection	Thermistors		

Note IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16
Färg svart

