

# SWE315LA-6 110KW 400/690V B5

## Three-phase asynchronous motor in cast iron

Motor type SWE315LA-6 110KW 400/690V B5  
Brand BUSCK  
Item number 93063172

| Voltage V | Power kW | Frequency Hz | Current A | Speed rpm |
|-----------|----------|--------------|-----------|-----------|
| 400       | 110      | 50           | 198,0     | 990       |
| 690       | 110      | 50           | 113,9     | 990       |
| 460       | 126,5    | 60           | 198,0     | 1188      |

|                        |              |                          |                      |
|------------------------|--------------|--------------------------|----------------------|
| Duty                   | S1           | Efficiency class         | IE3                  |
| Enclosure              | IP55         | Efficiency, load 100%    | 95,6                 |
| Insulation class       | F            | Efficiency, load 75%     | 95,6                 |
| Cooling                | IC411 (TEFC) | Efficiency, load 50%     | 94,6                 |
| Max. ambient temp.     | 40°C         | Power fact, load 100%    | 0,84                 |
| Min. ambient temp.     | -20°C        |                          |                      |
| Max. temp. rise        | 80 K         | Painting                 | Standard             |
| Max altitude, masl     | 1000         | Color                    | RAL 9005             |
|                        |              | Weight kg                | 1135                 |
| Torque, Nm             | 1061         | Sound pressure Lp dB(A)  | 70                   |
| Starting torque ratio  | 2,3          | Balance grade            | Normal               |
| Pull out torque ratio  | 2,3          | Inertia kgm <sup>2</sup> | 5,762                |
| Starting current ratio | 6,7          | Cable entries            | 2xM63 + 1xM16 (FL21) |
| Winding protection     | Thermistors  |                          |                      |

Note IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16  
Färg svart

