

SWE315LB-6 132KW 400/690V B5


Three-phase asynchronous motor in cast iron

Motor type SWE315LB-6 132KW 400/690V B5
 Brand BUSCK
 Item number 93063182

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	132	50	234,0	990
690	132	50	134,6	990
460	151,8	60	234,0	1188

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	95,7
Insulation class	F	Efficiency, load 75%	95,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,6
Max. ambient temp.	40°C	Power fact, load 100%	0,85
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	1205
Torque, Nm	1273	Sound pressure Lp dB(A)	70
Starting torque ratio	2,3	Bearing DE	NU319
Pull out torque ratio	2,3	Bearing NDE	6319
Starting current ratio	6,7	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	5,789
		Cable entries	2xM63 + 1xM16 (FL21)

Note IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16
 Färg svart
 Axel 90x170



D	E	F	G	GA	DH	M	N	P	S	T	AC	HD	LA	LD	L
90	170	25	81			600	550	660	24	6	680	830	22		1385