

SWE160L-8 7,5KW 400/690V B35

Three-phase asynchronous motor in cast iron

Motor type SWE160L-8 7,5KW 400/690V B35
Brand BUSCK
Item number 93081624w

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	7,5	50	16,8	730
690	7,5	50	9,66	730
460	8,63	60	16,8	876

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	88,2
Insulation class	F	Efficiency, load 75%	88,1
Cooling	IC411 (TEFC)	Efficiency, load 50%	86,3
Max. ambient temp.	40°C	Power fact, load 100%	0,73
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	110
Torque, Nm	98	Sound pressure Lp dB(A)	53
Starting torque ratio	2,0	Bearing DE	6209-2Z/C3
Pull out torque ratio	2,2	Bearing NDE	6209-2Z/C3
Starting current ratio	6,0	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	0,102
		Cable entries	2xM32 + 1xM16 (FL13)

Note IE3, Kopplingslåda med FL13, 2 x M40 + 1 x M16

