

SWE200L-8 15KW 400/690V 35

Three-phase asynchronous motor in cast iron

Motor type SWE200L-8 15KW 400/690V 35
Brand BUSCK
Item number 93082004

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	15	50	32,3	735
690	15	50	18,6	735
460	17,25	60	32,3	882

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	90,6
Insulation class	F	Efficiency, load 75%	90,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	89,1
Max. ambient temp.	40°C	Power fact, load 100%	0,74
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	250
Torque, Nm	195	Sound pressure Lp dB(A)	55
Starting torque ratio	2	Bearing DE	6312
Pull out torque ratio	2,3	Bearing NDE	6212
Starting current ratio	6,6	Balance grade	Normal
		Inertia kgm ²	0,395
		Cable entries	2xM50, 1xM16

Note IE3, Kopplingslåda med FL21, 2x M50 + 1 x M16
Färg svart

