

T3CR160MA-2 11KW 230/400V B3

Three-phase asynchronous motor in cast iron

Motor type T3CR160MA-2 11KW 230/400V B3
 Brand BUSCK
 Item number 93A21601T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	11	50	33,6	2930
400	11	50	19,3	2930
460	12,65	60	19,3	3516

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	91,2
Insulation class	F	Efficiency, load 75%	93,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	93
Max. ambient temp.	45°C	Power fact, load 100%	0,90
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	35,85	Weight kg	113
Starting torque ratio	2,5	Sound pressure Lp dB(A)	86
Pull up torque ratio	1,4	Bearing DE	6309 C3
Pull out torque ratio	3	Bearing NDE	6309 C3
Starting current ratio	9,5	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	0,05178
This motor has DNV type approval		Cable entries	2xM32, 1xM16

Note IE3

