

T3A160MA-2 11KW 230/400V B5

Three-phase asynchronous motor in aluminum

Motor type T3A160MA-2 11KW 230/400V B5
Brand BUSCK
Item number 93A21602

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	11	50	34,4	2960
400	11	50	19,8	2960
460	12,65	60	19,8	3552


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 35,5
Starting torque ratio 3,2
Pull up torque ratio 1,4
Pull out torque ratio 4
Starting current ratio 10,3
Winding protection Thermistors
This motor has DNV type approval

Efficiency class IE3
Efficiency, load 100% 91,2
Efficiency, load 75% 91,0
Efficiency, load 50% 89,6
Power fact, load 100% 0,88

Painting Standard
Color RAL 9005
Weight kg 85,5
Sound pressure Lp dB(A) 86
Bearing DE 6309-2Z/C3
Bearing NDE 6209-2Z/C3
Balance grade Normal
Inertia kgm² 0,05961337
Cable entries 2xM32, 1xM16

Note IE3 Färg svart



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no