

SWE160MA-2 11KW 230/400V B5

Three-phase asynchronous motor in cast iron

Motor type SWE160MA-2 11KW 230/400V B5
Brand BUSCK
Item number 93A21602w

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	11	50	33,6	2935
400	11	50	19,3	2935
460	12,65	60	19,3	3522

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	91,6
Insulation class	F	Efficiency, load 75%	91,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	90,5
Max. ambient temp.	40°C	Power fact, load 100%	0,90
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	113
Torque, Nm	35,8	Sound pressure Lp dB(A)	69
Starting torque ratio	2,2	Bearing DE	6209-2Z/C3
Pull out torque ratio	2,6	Bearing NDE	6209-2Z/C3
Starting current ratio	7,6	Balance grade	Normal
		Inertia kgm ²	0,0655
Note	IE3, Kopplingslåda med kabelanslutning Färg svart		
	Cable 3 x 25 + 1 x M16 + 1 x M16 + 1 x M16 (FL13)		

