

T3A160MA-2 11KW 230/400V B35


Three-phase asynchronous motor in aluminum

Motor type T3A160MA-2 11KW 230/400V B35
Brand BUSCK
Item number 93A21604

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	11	50	34,4	2960
400	11	50	19,8	2960
460	12,65	60	19,8	3552

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	91,2
Insulation class	F	Efficiency, load 75%	91,0
Cooling	IC411 (TEFC)	Efficiency, load 50%	89,6
Max. ambient temp.	45°C	Power fact, load 100%	0,88
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	85,5
Torque, Nm	35,5	Sound pressure Lp dB(A)	86
Starting torque ratio	3,2	Bearing DE	6309-2Z/C3
Pull up torque ratio	1,4	Bearing NDE	6209-2Z/C3
Pull out torque ratio	4	Balance grade	Normal
Starting current ratio	10,3	Inertia kgm ²	0,05961337
Winding protection	Thermistors	Cable entries	2xM32, 1xM16
This motor has DNV type approval			

Note IE3 Färg svart



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no