

T3CR225M-2 45KW 230/400V B3

Three-phase asynchronous motor in cast iron

Motor type T3CR225M-2 45KW 230/400V B3
 Brand BUSCK
 Item number 93A22251T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	45	50	132,1	2950
400	45	50	75,9	2950
460	51,75	60	75,9	3540

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	94
Insulation class	F	Efficiency, load 75%	94,6
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,1
Max. ambient temp.	45°C	Power fact, load 100%	0,91
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	145,68	Weight kg	237
Starting torque ratio	2,5	Sound pressure Lp dB(A)	92
Pull up torque ratio	1,4	Bearing DE	6313 C3
Pull out torque ratio	2,5	Bearing NDE	6313 C3
Starting current ratio	8,5	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,34366
This motor has DNV type approval		Cable entries	2xM50, 1xM16

Note IE3

