

SWE315LA-2 160KW 230/400V B5

Three-phase asynchronous motor in cast iron

Motor type SWE315LA-2 160KW 230/400V B5
Brand BUSCK
Item number 93A23172

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	160	50	459,1	2980
400	160	50	264,0	2980
460	184	60	264,0	3576

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	96
Insulation class	F	Efficiency, load 75%	96
Cooling	IC411 (TEFC)	Efficiency, load 50%	95,5
Max. ambient temp.	40°C	Power fact, load 100%	0,91
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	1100
Torque, Nm	513	Sound pressure Lp dB(A)	82
Starting torque ratio	2	Balance grade	Normal
Pull out torque ratio	2,2	Inertia kgm ²	1,967
Starting current ratio	7,6	Cable entries	2xM63 + 1xM16 (FL21)
Winding protection	Thermistors		

Note IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16
Färg svart

