

# T3A132S-4 5,5KW 230/400V B14


## Three-phase asynchronous motor in aluminum

Motor type T3A132S-4 5,5KW 230/400V B14  
Brand BUSCK  
Item number 93A41323

| Voltage V | Power kW | Frequency Hz | Current A | Speed rpm |
|-----------|----------|--------------|-----------|-----------|
| 230       | 5,5      | 50           | 18,3      | 1460      |
| 400       | 5,5      | 50           | 10,5      | 1460      |
| 460       | 6,33     | 60           | 10,5      | 1752      |

|                                  |                |                          |              |
|----------------------------------|----------------|--------------------------|--------------|
| Duty                             | S1             | Efficiency class         | IE3          |
| Enclosure                        | IP55           | Efficiency, load 100%    | 89,6         |
| Insulation class                 | F              | Efficiency, load 75%     | 89,8         |
| Cooling                          | IC411 (TEFC)   | Efficiency, load 50%     | 89,4         |
| Max. ambient temp.               | 45°C           | Power fact, load 100%    | 0,84         |
| Min. ambient temp.               | -20°C          |                          |              |
| Max. temp. rise                  | 80 K           | Painting                 | Standard     |
| Max altitude, masl               | 1000           | Color                    | RAL 9005     |
|                                  |                | Weight kg                | 47,4         |
| Torque, Nm                       | 35,9           | Sound pressure Lp dB(A)  | 71           |
| Starting torque ratio            | 2,3            | Bearing DE               | 6308-2Z/C3   |
| Pull up torque ratio             | 1,9            | Bearing NDE              | 6208-2Z/C3   |
| Pull out torque ratio            | 3,5            | Balance grade            | Normal       |
| Starting current ratio           | 9              | Inertia kgm <sup>2</sup> | 0,03446419   |
| Winding protection               | Thermocontacts | Cable entries            | 2xM25, 1xM16 |
| This motor has DNV type approval |                |                          |              |

Note IE3, Termokontakter



**BUSCK**  
www.busck.eu

Busck & Co AB  
Gamla Riksvägen 14  
428 32 Göteborg  
Sweden  
556027-1990  
info@busck.se

Busck & Co ApS  
Postboks 108  
0900 København C  
Denmark  
info@busck.eu

Busck AS  
Skibåsen 35C  
4636 Kristiansand  
Norway  
info@busck.no