

T3A160M-4 11KW 230/400V B35

Three-phase asynchronous motor in aluminum

Motor type T3A160M-4 11KW 230/400V B35
Brand BUSCK
Item number 93A41604

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	11	50	36,4	1470
400	11	50	20,9	1470
460	12,65	60	20,9	1764

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	91,4
Insulation class	F	Efficiency, load 75%	91,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	89,8
Max. ambient temp.	45°C	Power fact, load 100%	0,83
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	89
Torque, Nm	72	Sound pressure Lp dB(A)	75
Starting torque ratio	2,6	Bearing DE	6309-2Z/C3
Pull up torque ratio	1,8	Bearing NDE	6209-2Z/C3
Pull out torque ratio	2,8	Balance grade	Normal
Starting current ratio	7,6	Inertia kgm ²	0,1053728
Winding protection	Thermistors	Cable entries	2xM32, 1xM16
This motor has DNV type approval			

Note IE3 Färg svart

