

T3CR225S-4 37KW 230/400V B3

Three-phase asynchronous motor in cast iron

Motor type T3CR225S-4 37KW 230/400V B3
 Brand BUSCK
 Item number 93A42251T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	37	50	113,7	1470
400	37	50	65,4	1470
460	42,55	60	65,4	1764

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	93,9
Insulation class	F	Efficiency, load 75%	95,2
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,3
Max. ambient temp.	45°C	Power fact, load 100%	0,87
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	240,37	Weight kg	300
Starting torque ratio	2,5	Sound pressure Lp dB(A)	81
Pull up torque ratio	1,4	Bearing DE	6313 C3
Pull out torque ratio	2,5	Bearing NDE	6313 C3
Starting current ratio	9,2	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	0,57838
This motor has DNV type approval		Cable entries	2xM50, 1xM16

Note IE3

