


SWE250M-4 55KW 230/400V B5

Three-phase asynchronous motor in cast iron

Motor type SWE250M-4 55KW 230/400V B5
Brand BUSCK
Item number 93A42502

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	55	50	165,2	1490
400	55	50	95,0	1490
460	63,25	60	95,0	1788

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	95
Insulation class	F	Efficiency, load 75%	95
Cooling	IC411 (TEFC)	Efficiency, load 50%	93,8
Max. ambient temp.	40°C	Power fact, load 100%	0,88
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	391
Torque, Nm	353	Sound pressure Lp dB(A)	68
Starting torque ratio	2,3	Bearing DE	6314
Pull out torque ratio	2,7	Bearing NDE	6313
Starting current ratio	7,3	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,841
		Cable entries	2xM63 + 1xM16 (FL21)
Note	IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16 Färg svart		



D	E	F	G	GA	DH	M	N	P	S	T	AC	HD	LA	LD	L
65	140	18	58	69	M20	500	450	550	18.5	5	485	647	22	212	915