

T3CR250M-4 55KW 230/400V B35

Three-phase asynchronous motor in cast iron

Motor type T3CR250M-4 55KW 230/400V B35
 Brand BUSCK
 Item number 93A42504T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	55	50	165,8	1470
400	55	50	95,4	1470
460	63,25	60	95,4	1764

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	94,6
Insulation class	F	Efficiency, load 75%	95,2
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,5
Max. ambient temp.	45°C	Power fact, load 100%	0,88
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	357,31	Weight kg	391
Starting torque ratio	2,5	Sound pressure Lp dB(A)	83
Pull up torque ratio	1,8	Bearing DE	6314 C3
Pull out torque ratio	2,5	Bearing NDE	6314 C3
Starting current ratio	8,5	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	0,76504
This motor has DNV type approval		Cable entries	2xM63, 1xM16

Note IE3

