

T3CR280S-4 75KW 230/400V B5

Three-phase asynchronous motor in cast iron

Motor type T3CR280S-4 75KW 230/400V B5
Brand BUSCK
Item number 93A42802T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	75	50	227,8	1480
400	75	50	131,0	1480
460	86,25	60	131,0	1776

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	95
Insulation class	F	Efficiency, load 75%	95,1
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,8
Max. ambient temp.	45°C	Power fact, load 100%	0,87
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	483,95	Weight kg	520
Starting torque ratio	2,5	Sound pressure Lp dB(A)	86
Pull up torque ratio	1,8	Bearing DE	6316 C3
Pull out torque ratio	2,8	Bearing NDE	6316 C3
Starting current ratio	10	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	1,99603
This motor has DNV type approval		Cable entries	2xM63, 1xM16

Note IE3

