

T3CR225M-6 30KW 230/400V B5

Three-phase asynchronous motor in cast iron

Motor type T3CR225M-6 30KW 230/400V B5
Brand BUSCK
Item number 93A62252T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	30	50	92,1	975
400	30	50	53,0	975
460	34,5	60	53,0	1170

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	92,9
Insulation class	F	Efficiency, load 75%	93,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	90,9
Max. ambient temp.	45°C	Power fact, load 100%	0,88
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	293,85	Weight kg	305
Starting torque ratio	1,8	Sound pressure Lp dB(A)	76
Pull up torque ratio	1,5	Bearing DE	6313 C3
Pull out torque ratio	2,2	Bearing NDE	6313 C3
Starting current ratio	8	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,67058
This motor has DNV type approval		Cable entries	2xM50, 1xM16

Note IE3

