

SWE280M-6 55KW 230/400V B35

Three-phase asynchronous motor in cast iron

Motor type SWE280M-6 55KW 230/400V B35
Brand BUSCK
Item number 93A62814

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	55	50	173,6	985
400	55	50	99,8	985
460	63,25	60	99,8	1182

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	94,7
Insulation class	F	Efficiency, load 75%	94,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	93
Max. ambient temp.	40°C	Power fact, load 100%	0,84
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	562
Torque, Nm	533	Sound pressure Lp dB(A)	60
Starting torque ratio	2,2	Bearing DE	6317
Pull out torque ratio	2,2	Bearing NDE	6314
Starting current ratio	6,8	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm ²	1,988
		Cable entries	2xM63 + 1xM16 (FL21)

Note IE3, Kopplingslåda med FL21, 2x M63 + 1 x M16
Färg svart

