

SWE355MB-6 200KW 230/400V B3

Three-phase asynchronous motor in aluminum

Motor type SWE355MB-6 200KW 230/400V B3
Brand BUSCK
Item number 93A63561

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	200	50	600,0	995
400	200	50	345,0	995
460	230	60	345,0	1194

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	96,1
Insulation class	F	Efficiency, load 75%	96,2
Cooling	IC411 (TEFC)	Efficiency, load 50%	95,5
Max. ambient temp.	40°C	Power fact, load 100%	0,87
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	1905
Torque, Nm	1920	Sound pressure Lp dB(A)	70
Starting torque ratio	2,2	Bearing DE	NU322
Pull out torque ratio	2,2	Bearing NDE	6322
Starting current ratio	6,6	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	11,5
		Cable entries	2xM63 + 1xM16 (FL33)

Note IE3, Kopplingslåda med FL33, 2x M63 + 1 x M16
Färg svart

