

T3A90L-2 2,2KW 400/690V B5

Three-phase asynchronous motor in aluminum

Motor type T3A90L-2 2,2KW 400/690V B5
Brand BUSCK
Item number 93B20912

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	2,2	50	4,5	2897
690	2,2	50	2,59	2897
460	2,53	60	4,5	3476

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	86
Insulation class	F	Efficiency, load 75%	86,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	85,6
Max. ambient temp.	45°C	Power fact, load 100%	0,84
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	16,3
Torque, Nm	7,3	Sound pressure Lp dB(A)	72
Starting torque ratio	3,3	Bearing DE	6205-2Z/C3
Pull up torque ratio	2,2	Bearing NDE	6205-2Z/C3
Pull out torque ratio	3,4	Balance grade	Normal
Starting current ratio	8,6	Inertia kgm ²	0,0027
Winding protection	Thermocontacts	Cable entries	1xM20
This motor has DNV type approval			

Note IE3, Termokontakter

