

T3A90L-2 2,2KW 400/690V B35

Three-phase asynchronous motor in aluminum

Motor type T3A90L-2 2,2KW 400/690V B35
Brand BUSCK
Item number 93B20914

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	2,2	50	4,5	2897
690	2,2	50	2,59	2897
460	2,53	60	4,5	3476


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 7,3
Starting torque ratio 3,3
Pull up torque ratio 2,2
Pull out torque ratio 3,4
Starting current ratio 8,6
Winding protection Thermocontacts
This motor has DNV type approval

Efficiency class IE3
Efficiency, load 100% 86
Efficiency, load 75% 86,7
Efficiency, load 50% 85,6
Power fact, load 100% 0,84

Painting Standard
Color RAL 9005
Weight kg 16,3
Sound pressure Lp dB(A) 72
Bearing DE 6205-2Z/C3
Bearing NDE 6205-2Z/C3
Balance grade Normal
Inertia kgm² 0,0027
Cable entries 1xM20

Note IE3, Termokontakter



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no