

T3A132SA-2 5,5KW 500V B34

Three-phase asynchronous motor in aluminum


Motor type T3A132SA-2 5,5KW 500V B34
Brand BUSCK
Item number 93C21325

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
500	5,5	50	8	2932
575	6,33	60	8	3518

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	89,5
Insulation class	F	Efficiency, load 75%	89,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	88,5
Max. ambient temp.	45°C	Power fact, load 100%	0,89
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	43,4
Torque, Nm	17,9	Sound pressure Lp dB(A)	80
Starting torque ratio	3,2	Bearing DE	6308-2Z/C3
Pull up torque ratio	2,5	Bearing NDE	6208-2Z/C3
Pull out torque ratio	4	Balance grade	Normal
Starting current ratio	9,9	Inertia kgm ²	0,0155
Winding protection	Thermocontacts	Cable entries	2xM25, 1xM16

This motor has DNV type approval

Note IE3, Termokontakter



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no