

# T3A100L-6 1,5KW 500V B5

## Three-phase asynchronous motor in aluminum

Motor type T3A100L-6 1,5KW 500V B5  
Brand BUSCK  
Item number 93C61002

| Voltage V | Power kW | Frequency Hz | Current A | Speed rpm |
|-----------|----------|--------------|-----------|-----------|
| 500       | 1,5      | 50           | 3         | 950       |
| 575       | 1,73     | 60           | 3         | 1140      |

|                                  |                |                          |              |
|----------------------------------|----------------|--------------------------|--------------|
| Duty                             | S1             | Efficiency class         | IE3          |
| Enclosure                        | IP55           | Efficiency, load 100%    | 82,4         |
| Insulation class                 | F              | Efficiency, load 75%     | 83,8         |
| Cooling                          | IC411 (TEFC)   | Efficiency, load 50%     | 82,9         |
| Max. ambient temp.               | 45°C           | Power fact, load 100%    | 0,74         |
| Min. ambient temp.               | -20°C          |                          |              |
| Max. temp. rise                  | 80 K           | Painting                 | Standard     |
| Max altitude, masl               | 1000           | Color                    | RAL 9005     |
|                                  |                | Weight kg                | 22,1         |
| Torque, Nm                       | 15             | Sound pressure Lp dB(A)  | 61           |
| Starting torque ratio            | 2,1            | Bearing DE               | 6206-2Z/C3   |
| Pull up torque ratio             | 2,1            | Bearing NDE              | 6206-2Z/C3   |
| Pull out torque ratio            | 2,6            | Balance grade            | Normal       |
| Starting current ratio           | 5              | Inertia kgm <sup>2</sup> | 0,0078       |
| Winding protection               | Thermocontacts | Cable entries            | 1xM20, 1xM16 |
| This motor has DNV type approval |                |                          |              |

Note IE3, Termokontakter

