

SWE200LA-6 18,5KW 500V B5

Three-phase asynchronous motor in cast iron


Motor type SWE200LA-6 18,5KW 500V B5
Brand BUSCK
Item number 93C62002

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
500	18,5	50	28,3	980
575	21,28	60	28,3	1176

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	92,1
Insulation class	F	Efficiency, load 75%	92
Cooling	IC411 (TEFC)	Efficiency, load 50%	90,8
Max. ambient temp.	40°C	Power fact, load 100%	0,82
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	231
Torque, Nm	180	Sound pressure Lp dB(A)	59
Starting torque ratio	2,2	Bearing DE	6312
Pull out torque ratio	2,2	Bearing NDE	6212
Starting current ratio	7,4	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,384
		Cable entries	2xM50 + 1xM16 (FL21)

Note

Färg svart



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no