

SWE250M-6 37KW 500V B3

Three-phase asynchronous motor in cast iron


Motor type SWE250M-6 37KW 500V B3
 Brand BUSCK
 Item number 93C62501

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
500	37	50	53,8	985
575	42,55	60	53,8	1182

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	93,8
Insulation class	F	Efficiency, load 75%	93,9
Cooling	IC411 (TEFC)	Efficiency, load 50%	93
Max. ambient temp.	40°C	Power fact, load 100%	0,85
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	390
Torque, Nm	359	Sound pressure Lp dB(A)	59
Starting torque ratio	2,2	Bearing DE	6314
Pull out torque ratio	2,2	Bearing NDE	6313
Starting current ratio	7,2	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	0,113
		Cable entries	2xM63 + 1xM16 (FL21)

Note

Färg svart



A	B	B1	C	H	D	E	F	G	DH	GA	AA	AB	AC	HA	HD	BB	LD	L
406	349		168	250	65	140	18	58	M20	69	97	485	485	32	622	445	352	915