

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type: WP-DA100LTF IE3 4HP 4P 265/460V 60Hz B3

Motor item number: 100W000844T

Performance figures are subject to IEC tolerances.

50 HZ data	Rated power:	kW	3,0 (4HP) kW		
	Poles(Synch speed):	r.p.m	4p (1800) r.p.m		
	Full load speed:	r.p.m	1740 r.p.m		
	Voltage:	V	265	/	460 V
	Frequency:	Hz	60 Hz		
	Connection:		Δ	/	Y
	Amps full load (FLA):	A	9,1	/	5,3 A
	Amps no-load (NLA):	A	2,9@460V A		

Enclosure:	IP55	Cable entries size:	2 x CM20
Mounting:	IM B3 (IM 1001)	Winding protection:	N/A
Insulation Class:	F	Max. Altitude a.s.l.:	1000 m
Max. ambient temp.:	40 °C	Heater:	N/A
Min. ambient temp.:	-20 °C	Shaft extension:	28x60 mm
Max. temp. rise:	80 K	Weight:	34 kg
Duty type:	S1	Painting:	Standard
Cooling form:	IC411 (TEFC)	Color:	RAL 5021
Bearing DE	6206 ZZ C3 LF	Box position:	Top DE
Bearing NDE	6205 ZZ C3 LF	Cable entry towards:	Right
Grease:	NSK EA6	Cable type:	N/A
Regreasing facilities:	NO	Balance grade:	Normal

Efficiency class:	IE3	Sound pressure (1m):	54 dB(A)
Load data:	100%	Resistance PH R20:	1,64 Ω
Efficiency:	89,5		
Power factor:	0,80		

Full load torque (FLT):	16,5 Nm		
Starting torque ratio:	2,7 MA/MN		
Starting current ratio:	7,75 IA/IN		

Special remarks: metric motor acc to UL/CSA; Nema Premium;
--

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks:
