

T3AB80A-2 0,75KW 230/400V B3

Three-phase asynchronous brake motor in aluminum

Motor type T3AB80A-2 0,75KW 230/400V B3
Brand BUSCK
Item number B3020801e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	2,96	2890
400	0,75	50	1,7	2890
460	0,86	60	1,7	3468

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	80,7
Insulation class	F	Efficiency, load 75%	80,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	77,2
Max. ambient temp.	40°C	Power fact, load 100%	0,81
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	10,81
Torque, Nm	2,48	Sound pressure Lp dB(A)	67
Starting torque ratio	3,1	Bearing DE	6204-2Z/C3
Pull up torque ratio	2,3	Bearing NDE	6204-2Z/C3
Pull out torque ratio	3,2	Balance grade	Normal
Starting current ratio	7,4	Inertia kgm2	0,000972153
Note	Brake motor IE3	Brake torque, Nm	8

