

MSBCCL100L-2 3KW 230/400V B14

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL100L-2 3KW 230/400V B14
Brand BUSCK
Item number B3021003

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	3	50	10,49	2840
400	3	50	6,03	2840
460	3,45	60	6,03	3408


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 10,09
Starting torque ratio 2,2
Pull up torque ratio 1,4
Pull out torque ratio 2,3
Starting current ratio 7

Efficiency class EFF2
Efficiency, load 100% 82,6
Power fact, load 100% 0,87

Painting Standard
Color RAL 9005
Weight kg 27
Sound pressure Lp dB(A) 76
Bearing DE 6206-2Z/C3
Bearing NDE 6206-2Z/C3
Balance grade Normal
Inertia kgm² 0,0036
Cable entries 1xM20

Brake torque, Nm 23



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no