

MSBCCL132SA-2 5,5KW 400/690V B14

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL132SA-2 5,5KW 400/690V B14
Brand BUSCK
Item number B3021323

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	5,5	50	10,53	2900
690	5,5	50	6,05	2900
460	6,33	60	10,53	3480



Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 18,11
Starting torque ratio 2
Pull up torque ratio 1,2
Pull out torque ratio 2,2
Starting current ratio 7,5

Efficiency class EFF2
Efficiency, load 100% 85,7
Power fact, load 100% 0,88

Painting Standard
Color RAL 9005
Weight kg 42
Sound pressure Lp dB(A) 80
Bearing DE 6308-2Z/C3
Bearing NDE 6208-2Z/C3
Balance grade Normal
Inertia kgm² 0,0119
Cable entries 2xM25

Brake torque, Nm 80



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no