

MSBCCL80A-4 0,55KW 230/400V B35

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL80A-4 0,55KW 230/400V B35
Brand BUSCK
Item number B3040804

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,55	50	2,75	1370
400	0,55	50	1,58	1370
460	0,63	60	1,58	1644


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 3,83
Starting torque ratio 2,2
Pull up torque ratio 1,7
Pull out torque ratio 2,4
Starting current ratio 6

Efficiency class EFF2
Efficiency, load 100% 67
Power fact, load 100% 0,75

Painting Standard
Color RAL 9005
Weight kg 11
Sound pressure Lp dB(A) 58
Bearing DE 6204-2Z/C3
Bearing NDE 6204-2Z/C3
Balance grade Normal
Inertia kgm² 0,00128
Cable entries 1xM20

Brake torque, Nm 8



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no