

MSBCCL80B-4 0,75KW 230/400V B3

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL80B-4 0,75KW 230/400V B3
 Brand BUSCK
 Item number B3040811

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	3,36	1380
400	0,75	50	1,93	1380
460	0,86	60	1,93	1656

Duty S1
 Enclosure IP55
 Insulation class F
 Cooling IC411 (TEFC)
 Max. ambient temp. 40°C
 Min. ambient temp. -20°C
 Max. temp. rise 80 K
 Max altitude, masl 1000

Torque, Nm 5,19
 Starting torque ratio 2,2
 Pull up torque ratio 1,5
 Pull out torque ratio 2,4
 Starting current ratio 6

Efficiency class EFF2
 Efficiency, load 100% 72
 Power fact, load 100% 0,78

Painting Standard
 Color RAL 9005
 Weight kg 12
 Sound pressure Lp dB(A) 58
 Bearing DE 6204-2Z/C3
 Bearing NDE 6204-2Z/C3
 Balance grade Normal
 Inertia kgm² 0,0015
 Cable entries 1xM20

Brake torque, Nm 12

