

MSBCCL90S-4 1,1KW 230/400V B14

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL90S-4 1,1KW 230/400V B14
Brand BUSCK
Item number B3040903

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	1,1	50	4,59	1400
400	1,1	50	2,64	1400
460	1,27	60	2,64	1680


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 7,5
Starting torque ratio 2,2
Pull up torque ratio 1,5
Pull out torque ratio 2,4
Starting current ratio 6

Efficiency class EFF2
Efficiency, load 100% 76,2
Power fact, load 100% 0,79

Painting Standard
Color RAL 9005
Weight kg 15
Sound pressure Lp dB(A) 61
Bearing DE 6205-2Z/C3
Bearing NDE 6205-2Z/C3
Balance grade Normal
Inertia kgm² 0,00221
Cable entries 1xM20

Brake torque, Nm 16



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no